

Claims

1. A microprocessor, comprising:
- 5 registers for holding values, wherein said registers are logically partitioned into register windows;
- a storage for storing values held in the registers of the register windows;
- a detector for detecting that one of a register window overflow condition and a register window underflow condition is imminent; and
- 10 an instruction generator responsive to the detector for generating at least one instruction to manipulate the storage to avoid a trap responsive to the condition that is detected as imminent.
2. The microprocessor of claim 1, wherein the detector and the instruction generator are implemented in hardware.
- 15 3. The microprocessor of claim 1, wherein the microprocessor further comprises a cache for caching instructions for introduction into an execution stage and wherein the detector examines the instructions in the cache to determine if a register window overflow condition is imminent by determining if execution of any of the fetched instructions will result in a register window overflow condition.
- 20 4. The microprocessor of claim 3, wherein the detector looks for an instruction in the cache that stores contents of a register window in the registers when the registers have no available space for storing the contents.
- 25 5. The microprocessor of claim 3, wherein the detector examines how much storage space is available in the registers.
- 30 6. The microprocessor of claim 1, wherein the microprocessor further comprises a cache for caching instructions for introduction into an execution stage and wherein the detector examines the instructions in the cache to determine if a register window underflow condition is imminent by determining if execution of the instructions will result in a register window underflow condition.
- 35 7. The microprocessor of claim 6, wherein the detector looks for an instruction in the cache that restores a register window when contents of the register window are stored on the stack rather than in the registers.

8. The microprocessor of claim 1, wherein the detector detects solely whether a register window underflow condition is imminent.
- 5 9. The microprocessor of claim 1, wherein the detector detects solely whether a register window overflow condition is imminent.
10. The microprocessor of claim 1, wherein the detector detects both whether a register window overflow condition is imminent and whether a register window  
10 underflow condition is imminent.
11. The microprocessor of claim 1, wherein the microprocessor further comprises an execution unit for executing the instruction generated by the instruction generator.
- 15 12. The microprocessor of claim 1, wherein the microprocessor performs out of order execution of instructions.
13. The microprocessor of claim 1, wherein the instruction generator includes a second storage for holding the at least one instruction that is generated by the instruction  
20 generator.
14. In a microprocessor having a storage and registers, an engine, comprising:  
a detector for detecting that a trap requiring an access to the storage to  
manage register window information is imminent; and  
25 an instruction generator responsive to the detector for generating at least one instruction to avoid the trap.
15. The engine of claim 14, wherein the engine is implemented in hardware.
- 30 16. In a microprocessor having a plurality of registers logically partitioned into register windows and a storage for storing contents of register windows, a method, comprising the steps of:  
determining that one of a register window spill and a register window fill  
is imminent; and  
35 in response to determining that the register window spill is imminent, manipulating the storage to avoid a trap responsive to the spill or the fill determined as imminent.

5

10

[illegible]